

## PRODUCT SPECIFICATIONS - WIRING DIAGRAM

### CONTROLLER - IN ENCLOSURE

13.25" W x 13.375" H x 4.625" D  
Approximate Weight: 13.30 lbs

### CONTROLLER - BOARD ONLY

11.0" W x 8.0" H x 1.25" D  
Approximate Weight: 1.6 lbs

### SERIAL PORTS

HAI Lighting Control UPB PIM (#36A00-1)  
Leviton Z-Wave (#VRCOP), HAI ZigBee (#81A00-3)  
HAI Omni-Bus, Hi-Fi 2 (#95A00)  
Access Control Readers (#75A00, #54A00)  
Clipsal, Dynalite, Coolmaster, Serial Connectivity  
Cable (#36A05-4), Serial to PC Cable (#21A05-2)

### AUDIO

Omni Console w/ Spkr/Mic (#33A00-4)  
Surface Speaker/Mic (#28A00-1)  
Flush Speaker/Mic (#28A00-2)  
Two-Way Voice Module (#10A11-1)

### ETHERNET PORT

Snaplink for Windows,  
Snaplink Mobile for Android/  
iPhone and iOS, PC Access,  
OmniTouch 5.7e Touchscreen,  
OmniTouch Pro, HAI Omni-Bus

### 12V BATTERY

Two-Way X-10  
Interface Kit  
(#10A09-7)

### TELEPHONE INTERFACE

- Land line
- Cellular  
Communications  
Center (#70A00)
- PC Access

### EARTH GROUND

### TRANSFORMER 24V/40VA

### USER INTERFACE

OmniTouch 5.7 Touchscreen

Omni Cosoles (#33A00)

### EXPANSION

HAI Wireless Receiver (#45A00-1)  
Wireless Receiver for GE (#42A00-2)

### SECURITY & ENERGY MANAGEMENT

Temperature Sensor (#31A00-7)  
Temperature/Humidity Sensor (#31A00-8)  
Standard Security/Fire/Environmental  
Sensors

### COMFORT & CONVENIENCE

Omnistat2 Thermostats

HAI makes Visio stencils available to our dealers. HAI  
Omni systems are designed for professional installation.  
Licensing requirements vary by area.



California  
Title 24  
Compliant

CP-01  
Compliant