

Specifications

Serial Interface

Interface	Male DB9
Speed	1200bps ~ 115Kbps
Flow Control	None, Hardware
Pins	RS232: Rx, Tx, RTS, CTS, DTR, DSR, GND

Network Interface

Interface	10 Base-T Ethernet with RJ45
Protocols	ARP, IP/ICMP, TCP/IP, Telnet, DHCP client, PPPoE

Management

Management	Telnet, Serial console port & HelloDevice Manager
Security	User ID & Password

Indicator

LED Displays	Power/Ready/10 Base-T Link/Act, Serial Rx, Tx
---------------------	---

Power

Supply Power Voltage	7.5V ~ 15V DC
Supply Power Current	300mA / 7.5V DC

Operating Environment

Operating Temperature	5° C to 55° C
Storage Temperature	-40° C to 66° C

Packaging

Dimension (W x H x D)	100x 72 x 25 mm (3.94 x 2.83 x 0.98 inches)
Weight	240g

Regulatory Approvals

Approvals	FCC(A), CE, MIC
------------------	-----------------

OS Support

Microsoft	Win 98/ME/NT4/2000/XP/Vista
Linux	Linux x86
Unix	Unix98 pty driver (included in Linux by default)

Package Content

Product	LS100
Cable	Serial data cable
Power	External 110V power adapter
Manual	Quick start guide
CD	CD-ROM

Optional Accessories

DIN-Rail	DIN-Rail mount kit
-----------------	--------------------

Warranty

Warranty Period	5-year Limited Warranty
------------------------	-------------------------

Manufacturer

Company	Sena
----------------	------