



## SECURITRON SPECIFICATION DK-11 (STAND ALONE DIGITAL ENTRY KEYPAD)

### PRODUCT DATA SHEET

**PRODUCT NAME      DK-11 STAND ALONE DIGITAL ENTRY KEYPAD**

<p><b>System Description</b> <i>Basic use</i> <i>Limitations</i></p>	<p>The Securitron Magnalock Corporation DK-11 Stand Alone Digital Entry Keypad Securitron's DK-11 is a one piece digital keypad specifically designed for control of electric locks. It is furnished on a single gang, stainless steel outlet box cover with plastic backbox. It includes multiple code capability which is programmable from the keypad and a 5A SPDT timed, control relay output. Two LEDs are furnished. The green LED flashes as each key is pressed and the red LED turns on during the time that the DK-11 has released the door. Both LEDs also provide programming prompts.</p> <p>The DK-11 is not waterproof and is intended for interior use. However, an accessory cover (part # WCC) allows its use outside where direct, heavy rain is not expected. It should also not be employed in high security installations as with its one piece construction, an intruder could gain access to the electric lock power wires if he is able to dismount the DK-11. The power wires could then be shorted or opened (depending on the type of lock) to gain access.</p>
<p><b>References</b></p>	<p>ISO 9001.</p>
<p><b>Warranty</b></p> <p><b>Warranty Continued</b></p>	<p>SECURITRON MAGNALOCK CORPORATION warrants that it will replace at customer's request, at any time for any reason, products manufactured and branded by SECURITRON.</p> <p>SECURITRON will use its best efforts to ship a replacement product by next day air freight at no cost to the customer within 24 hours of SECURITRON's receipt of the product from customer. If the customer has an account with SECURITRON or a valid credit card, the customer may order an advance replacement product, whereby SECURITRON will charge the customer's account for the price of the product plus next day air freight, and will credit back to the customer the full amount of the charge, including outbound freight, upon SECURITRON's receipt of the original product from the customer.</p> <p>SECURITRON's sole and exclusive liability, and customer's sole remedy, is limited to the replacement of the SECURITRON product when delivered to SECURITRON's facility (freight and insurance charges prepaid by customer). The replacement, at SECURITRON's sole option, may be the identical item or</p>

SECURITRON MAGNALOCK CORP., 550 Vista Blvd., Sparks NV 89434 USA  
 Tel: (775) 355-5625 • (800) MAGLOCK • Fax: Mkt. (775) 355-5636, Fax: Admin. (775) 355-5633  
 Website: www.securitron.com • E-mail: info@securitron.com

	<p>a newer unit which serves as a functional replacement. In the event that the product type has become obsolete in SECURITRON's product line, this MAGNACARE warranty will not apply. This MAGNACARE warranty also does not apply to custom, built to order, or non-catalog items, items made by others (such as batteries), returns for payment, distributor stock reductions, returns seeking replacement with anything other than the identical product, or products installed outside of the United States or Canada. This MAGNACARE warranty also does not apply to removal or installation costs.</p> <p>SECURITRON will not be liable to the purchaser, the customer or anyone else for incidental or consequential damages arising from any defect in, or malfunction of, its products. SECURITRON does not assume any responsibility for damage or injury to person or property due to improper care, storage, handling, abuse, misuse, or an act of God.</p> <p>EXCEPT AS STATED ABOVE, SECURITRON MAKES NO WARRANTIES, EITHER EXPRESS OR IMPLIED, AS TO ANY MATTER WHATSOEVER, INCLUDING WITHOUT LIMITATION THE CONDITION OF ITS PRODUCTS, THEIR MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.</p>
<b>Other Information</b>	<p><b>Dimensions:</b> Single gang</p> <p><b>Operating Environment:</b> Indoor use. Outdoor weather cover for weather resistance.</p> <p><b>Temperature:</b> 0 to +70 degrees C +32 to +158 degrees F</p> <p><b>Visible/Audible Indicators:</b> Red and Green LEDs</p> <p><b>Construction:</b> Stainless steel backplate with 12 keys (10 digits and * and # keys).</p> <p><b>Power:</b> 12 or 24 volts VDC</p> <p><b>Current Draw:</b> 70 mA at 12 or 24 VDC</p>
<b>Accessories</b>	Weather cover.
<b>Finishes</b>	Touchtone type keypad mounted on stainless steel plate.
<b>Installation</b>	<p>Please refer to instruction manual (Securitron part number: 500-16500) Instruction manual can also be found on our website: <a href="http://www.securitron.com">www.securitron.com</a></p>

SECURITRON MAGNALOCK CORP., 550 Vista Blvd., Sparks NV 89434 USA  
 Tel: (775) 355-5625 • (800) MAGLOCK • Fax: Mkt. (775) 355-5636, Fax: Admin. (775) 355-5633  
 Website: [www.securitron.com](http://www.securitron.com) • E-mail: [info@securitron.com](mailto:info@securitron.com)

